



## COOL STONE

Cool stone is used to help keep buildings cool. It is applied to the layer of gravel (stones) used on flat tar roofs to reflect the heat away from the building. It's excellent adhesion properties make it a long-term solution with little to no maintenance. As a secondary benefit, it extends the life of the roof. Cool Stone works very well as a block filler for cindercrete block walls or very porous concrete surfaces.

Cool Stone is a two-component industrial coating developed exclusively for coating gravel on flat roofs. Cool Stone was engineered for long-term adhesion and to not deteriorate, crack or peel from long periods of exposure to UV, moisture and high heat.

### RECOMMENDED USE

Used on any building or structure with flat coal tar roofs and gravel.  
Used on cindercrete block walls.

### SPECIFICATIONS

UNIT SIZE: 5 gallon pail/9 Litre Jug  
COVERAGE: 1200 - 1500 square feet per Kit  
COLOR: White  
FOOT TRAFFIC: 2 hours  
SHELF LIFE: 1 yr unopened container  
APPLICATION TEMP: 10C (50 F) to 22C (72 F)  
Pot Life: 1- 2 hour  
VOC'S – Zero  
Meets **LEED Requirements**.

### SURFACE PREPARATION

The surface must be clean and dry.

### MIXING INSTRUCTIONS

Pour all of liquid component into a clean five-gallon pail and add the powder mixture and mix until smooth (approximately 1-2 minutes).

Spray on mixture using airless paint sprayer. May have to apply two coats on gravel to get proper coverage by spraying 1<sup>st</sup> coat in one direction at a 45 degree angle, and 2<sup>nd</sup> coat in opposite direction at a 45 degree angle.

For applications on cindercrete block wall apply using roller or sprayer. Once dry, coat with Cornerstone's Premium Acrylic to protect and give longer service life to the Cool Stone.

### CLEAN-UP

Clean all tools and equipment with water. Cured material may be removed by mechanical means only.

### WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supercedes all other warranties express or implied.