

CORNERSTONE COATINGS INC.

Voice: 1-306-369-2521 Cell: 369-7711 Fax: 1-306-369-2656

Email: murray@cornerstonecoatings.com Website: www.cornerstonecoatings.com

MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME: Cornerstone Industrial Consulting Ltd.

REGULAR PHONE: 1-306-369-2521

TRADE NAME: FIBER-LINK NYLON FIBER

ADDRESS: Box 479, Bruno, SK S0K 0S0

PRODUCT USE: Concrete Reinforcement Fiber

DOT HAZARD CLASS: N/A

DOT SHIPPING NAME: N/A

DOT LABEL: N/A

SECTION 2 - CHEMICAL FORMULATION

CHEMICAL FORMULA: N/A

CHEMICAL NAME: Adipic Acid-hearmethylenediamine fiber

CAS NO: 32131-17-2

US Surface Freight Classification: Synthetic Fiber

Reportable Quantity (RQ) (40CFR Part 117)

Under Clean Water Act Regulation: N/A

SECTION 3 - OCCUPATIONAL CONTROL PROCEDURES

EYE PROTECTION: Nylon concrete fiber does not cause significant eye irritation or eye toxicity requiring special protection. Avoid eye contact a good industrial practice.

SKIN PROTECTION: Nylon concrete fiber does not present significant skin concern requiring special protection.

RESPIRATORY PROTECTION: Avoid breathing dust. Use NIOSH/MSHA approved equipment when airborne exposure is excessive.

VENTILATION: No special precaution recommended.

SECTION 4 - PHYSICAL CHARACTERISTICS

TYPE: NYLON 6 CONCRETE FIBER

FLASH IGNITION TEMPERATURE: 581 - 592 Degrees F

AUTO IGNITION TEMPERATURE: 905 Degrees F

Method: ASTM-D 1929-77

EXTINGUISHING MEDIA: Water or class A extinguishing agent.

Appearance: Clear to White

Odor: Essentially odorless

Melting point: 490-510 Degrees F

SECTION 6 - WASTE DISPOSAL

May be disposed of in an approved incinerator or land fill. Consult your attorney or appropriate regulatory official for information on such disposal.

PREPARED BY: Cornerstone Industrial Consulting Ltd.

PHONE: (306) 369-2521

UPDATE: January 2010 UPDATE