

STUCCO MASTER ADDITIVE

Advanced System for Waterproofing

Stucco Master is a liquid which is added to traditional trowel applied stucco or spray coatings. Stucco Master enhances the strength and adhesion of the stucco and creates a moisture barrier from rain. This moisture barrier significantly reduces water leakage problems and mold growth associated with water penetration in many stucco homes. Stucco Master also significantly increases resistance to fading from sun exposure. Stucco Master also acts as a super plasticizer reducing the amount of water needed.

Water Resistance

Stucco Master stucco produces excellent water resistance, decreases spalling, cracking, and surface degradation caused by repeated freeze/thaw cycles, and resists numerous industrial chemicals and molds.

Increases Durability and Strength

Stucco Master stucco is hard, tough and durable, characteristics that are essential for exterior exposure. Stucco Master stucco has high flexural, tensile and impact strengths as well as excellent abrasion resistance and adhesion.

Resistance Properties

Stucco Master stucco resists yellowing, discoloration or fading due to exposure to exterior environments.

The Longest Pot Life

Stucco Master stucco has enhanced flow characteristics for spray coat applications and allows for less use of water. Stucco Master stucco has the longest mortar pot life in the industry. This is very important in warm weather, low humidity application conditions.

Meets **LEED Requirements**.

PHYSICAL CHARACTERISTICS

Appearance: Milky, White Liquid

Odor: Mild Odor

Ph (when packed): 9.3 - 10.2

Specific Gravity: 1.059

Lbs/Gal: 8.8

Freeze/Thaw Stability: 5 cycles min.

Film-Formation Temp. 10C or 50F

VOC's - Zero

SURFACE PREPARATION

The surface must be clean and sound.

Remove all loose and disintegrated material.

Remove all types of oil, dirt, dust, mold or mildew, efflorescence, release and curing agents.

SUGGESTED FORMULATION

Stucco Mix

1 bag @88 lb cement

1 bag @88 lb lime

6 bag@ 88 lb sand

4.4 liters Stucco Master

Remainder water for desired consistency

Each 5 gallon or 18.9 litre Stucco Master Additive generally will make enough stucco to cover 200 square metres, depending on the thickness of the finish coat.

CLEAN UP

Clean application tools and mixing equipment with water immediately following use, as hardened product is difficult to remove.

WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supercedes all other warranties express or implied.

LAST UPDATED: JULY 5, 2011