

PREMIUM ACRYLIC READY TO USE

The Ultimate Decorative High Sheen Finish Engineered Cross-Linking Technology

In the past, Acrylics were mainly used for cure and seals and sealing of warehouse floors. Only recently have acrylics been used in the exterior decorative concrete market.

A major shift in the use of acrylics however, has brought little to no change in the formulations of acrylics. For the most part, manufacturers have been taking these old cure and seal products, repackaging them at higher solids and re-marketing them to the exterior decorative concrete industry. Having the same products that were once used for interior flat work, now being used for exterior decorative concrete is quickly creating a number of problems for contractors. Exterior durability, UV resistance, hot tire resistance and maintaining a shine, are factors that the interior flat work market did not have to previously consider. Yet, it is vitally important to the ever-growing decorative concrete industry.

Cornerstone Coatings had to think outside the box to provide the Decorative Concrete Industry with the correct solution, an Acrylic that was engineered and designed for long-term exterior durability. Common problems occurring with other acrylics such as frosting, discoloration, peeling, loss of shine, and inter-coat adhesion can be eliminated by using Cornerstone's Premium Acrylic. Premium Acrylic outperforms other acrylic sealers by up to 5 times, because it is the strongest most durable formulation on the market for interior and exterior applications.

- ~VOC COMPLIANT 400 g/l
- ~Superior Interior and Exterior Durability
- ~Proven Hot Tire Resistance
- ~Long Term Gloss Retention
- ~Does Not Frost, Discolor, or leave a Milky Film
- ~UV Stable and Non-Yellowing

USES

All Horizontal Concrete/Stamped Concrete/Stained Concrete/Stenciled Concrete/Paving Stones/Exposed Aggregate Surfaces/Block Walls

PHYSICAL CHARACTERISTICS

VOC COMPLIANT – 400 grams/litre
Recommended Coats: Minimum of 2
Color: Water Clear
Flashpoint: 10.5 C
Exterior Durability: Excellent
Wearing Quality: Excellent
Ready to Use – 20% Equiv.
Coverage: Approximately 250 sq.ft/gal
Solvent for Cleaning Equipment: Xylene
Drytime: 1 - 2 hours at 77 F or 25 C
Food Safe: Approved
Packaging: 3.78 Litre/18.9 Litre/205 Litre

CAUTIONS

Do not use Premium Acrylic Ready to Use in combination with any other acrylic sealer or cure and seal other than Premium Acrylic Concentrate or Cornerstone's Advance Acrylics.

APPLICATION

SURFACE PREPARATION: Area to be sealed must be cleaned and free of all foreign matter such as dirt, rubber marks, paint etc. For best results remove other acrylic cure and seals before application of Premium Acrylic Ready to Use. Apply with a solvent resistant lint-free long nap roller or spray.

SEALING NEW CONCRETE

Do not dilute.

For Stamped Concrete/Stained Concrete/Overlays/Warehouse Floors/Driveways

1st Coat use Premium Acrylic Ready to Use for the best penetration and proper adhesion. For additional coats either use Premium Acrylic Ready to Use or dilute the Premium Acrylic Concentrate using a compatible solvent.

Applying over any other Acrylic Sealer

Remove existing sealer. Apply Premium Acrylic Ready to Use according to above instructions.

WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supercedes all other warranties express or implied.