

ADVANCE – C35

ACRYLIC BLEND CONCRETE SEALER

DESCRIPTION

The philosophy of Cornerstone Coatings has always been “to make a better product than what is currently available in the marketplace,” and we’ve done that with ADVANCE C35 Acrylic Blend Sealer.

Through our research and development team, we have perfected the encapsulating method whereby the typical acrylic resin widely used in the industry can be combined with the superior high-end acrylic resin used in Cornerstone’s Premium Acrylic. This encapsulating method diminishes the negative qualities of the typical acrylic and takes on the superior overall performance of the high-end resin.

Cornerstone Coatings is leading the way in this new technology with our low cost, advanced performing acrylic sealer that replaces the existing low cost, poor performing acrylic sealers in the marketplace.

BENEFITS

- ~VOC Compliant
- ~Superior Interior and Exterior Durability
- ~Increased Hot Tire Resistance
- ~Increased Gloss Retention
- ~Resists leaving a milky film
- ~UV Stable and Non-Yellowing

USES

All Horizontal Concrete/Stamped Concrete/Stained Concrete/Stenciled Concrete/Paving Stones/Exposed Aggregate Surfaces/Block Walls

PHYSICAL CHARACTERISTICS

Recommended Coats: Minimum of 2
Color: Water Clear
Flashpoint: 13 Celsius
Exterior Durability: Excellent
Wearing Quality: Excellent
Solids: 35% Equiv.
Coverage: Approximately 250 sq.ft/gal
Solvent for Cleaning Equipment: Xylene
Drytime: 1 - 2 hours at 77 F or 25 C
Packaging: 18.9 Litre/205 Litre
VOC’S: 400 grams/litre

CAUTIONS

Do not use Advance-C35 in combination with any other acrylic sealer or cure and seal.
Recommended waiting a minimum of 3 days before applying to green concrete.

APPLICATION

SURFACE PREPARATION: Area to be sealed must be cleaned and free of all foreign matter such as dirt, rubber marks, paint etc. For best results remove other acrylic cure and seals before application of Advance-C35. Apply with a solvent resistant lint-free long nap roller or spray. We recommend to apply a lower solids Advance Acrylic formulation for 1st coat, or dilute Advance-C35 with a compatible solvent for 1st coat.

WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supercedes all other warranties express or implied.

LAST UPDATED: JULY 5, 2011