

DECO ART

For Driveways, Pool Decks, Basement Floors

Deco Art is a thin overlay system or microtopping developed to decorate new or existing concrete. Regular boring concrete can now easily be transformed to look like tile, brick, or cobblestone with a wide range of color choices. Deco Art has become mainstream for beautifying homes and yards, because it allows for an extreme landscaping makeover for much less than traditional masonry work would cost. Deco Art is also used as a decorative wall coating. It comes in a white and grey base, enabling the contractor to create pastel colors or deep base colors. Simply add your own integral color to create custom work.

Another major benefit to contractors is that Deco Art has the longest pot life in the industry. This is vitally important for warm weather, low humidity applications. There is nothing more frustrating than halfway through the job, your product becomes unusable and must be thrown away. With Deco Art you can relax, you'll have plenty of time to work and get things right.

Deco Art is a product meant to go outside and handle exterior conditions. It is amazing what type of materials are being used by other companies. In the varied Canadian climate we have, and in the high moisture climates, you'll get into trouble if you are using an inferior product.

Deco Art is an extremely durable material that is stable in extreme weathers. It tenaciously adheres to concrete to provide long-term, trouble-free enjoyment. Deco Art is the simplest system available to the contractor. Simply mix the liquid into the powder mixture, and it's ready to be trowelled or sprayed. Once sealed with Premium Acrylic, the concrete will look great for years.

Meets **LEED Requirements**.

USES

For Driveways, Pool Decks, Basement Floors, Garage Pads, Patios, Walls

COVERAGE

Approximately 150-200 sq. ft. per 60 lb kit, per coat

APPLICATION

SURFACE PREPARATION

- The surface must be clean and sound. Remove all loose and disintegrated material. Remove all types of oil, dirt, dust, mold or mildew, efflorescence, release and curing agents. Do Not apply to any exterior wood surfaces.
- Always acid wash the surface prior to application.
- Apply 1 coat of Protec III Chem-RX to concrete surface as a pretreatment.

MIXING INSTRUCTIONS

- Always mechanically mix. Do not mix at a high speed.
- Pour all of liquid component into a clean five gallon pail, add the mortar mixture and mix until smooth (approximately 30 seconds).
- Let material sit 5 minutes to fatten, then re-mix for 10-15 seconds before installation.
- Apply your base coat and let it dry before placing stencil/tape. Higher air and surface temperatures will decrease working/placement time.
- Apply second coat over stencil/tape and let it set before removing the stencil/tape.
- Deco Art can be sprayed or trowelled.
- For normal use, allow a 24 hour curing period. For heavy wheeled traffic, allow a 4 day curing period.
- Seal Deco Art after 24 hours with Premium Acrylic.

CLEAN UP

Clean all tools and equipment with water. Cured material may be removed by mechanical means only.

WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supercedes all other warranties express or implied.

LAST UPDATED: JULY 5, 2011