

REPEL WATERPROOFING SEALER For Stucco

Repel is a highly reactive micro-emulsion that works specifically with the properties of stucco to block water and moisture penetration.

Simply spray Repel on existing stucco and allow to dry. Repel will not change the color or texture of the surface and will remain effective for 5 to 10 years depending on how harsh the environment is.

TECHNICAL DATA

- Reduces water absorption
- ASTM C-67. Maintaining greater than 50% breathability
- Will not alter color, texture, or any other physical characteristic of unsealed surfaces
- Improves resistance to freeze/thaw exposure
- Reduces penetration of grease, oils, acids, and salts
- VOC'S - ZERO
- Only one coat needed
- Leaves a clear natural finish
- Water clean-up
- FOOD SAFE APPROVED
- Meets **LEED Requirements**.

USES

To reduce efflorescence and improve resistance to effects of weathering on Stucco. To stop moisture migration.

COVERAGE

Approximately 100 Sq. Ft./4 Litres (dependent on porosity of surface)

CAUTIONS

- Due to Repel's properties, adhesives or other coating will not bond sufficiently.
- Protect surrounding area from over-spray, in case of accidental contact rinse thoroughly with water immediately.
- Care should be taken to protect nearby vegetation.
- DO NOT apply to frozen surfaces.
- Only ONE Coat is possible.
- This product is not meant to fill or seal visible cracks.
- For surfaces not specified in this Technical Data, or where surface may have been previously sealed, we recommend that Repel be applied to a small test area first, and observed for possible adverse reactions. Under certain conditions a precipitate of sodium carbonate may be deposited as Repel dries. To avoid this white precipitate

which is especially noticeable on old or dark surfaces observe the following precautions: Always test Repel on a small area to determine if these conditions exist. Substrates with a high acid level will more readily neutralize Repel before it is absorbed into the brick, leaving the residue on the surface.

SURFACE PREPARATION

- Make sure surface is clean, free of dirt, oil and other contaminants. Let surface dry 3 to 4 hours after cleaning before applying Repel.
- Patching and caulking must be done before applying Repel.
- Plastic or paper all glass and windows before applying Repel. Do NOT spray directly on the plastic or paper during application to avoid leaking or soaking through. Remove plastic or paper immediately after each side of the structure is complete.

APPLICATION

- For best results, spray Repel using a pump up sprayer, this will ensure proper coverage of joints, laps, butts, etc.
- Shake the container well before using.
- If the product has been frozen, thaw completely and shake well.
- Use Repel right out of the container. DO NOT dilute or mix with other liquids.
- Surface to receive Repel should be lightly dampened with clean water immediately prior to application.
- Apply Repel with a sprayer (20 to 30 psi). Apply liberally and saturate all areas.
- On vertical surfaces, avoid run-down, overlapping, or second coating.
- Repel must be applied starting from the top and working down the surface, keeping a wet edge. If Repel dries between passes "water spotting" may result.
- Only one application is possible.
- Repel sets within 2 to 4 hours.
- Full protection will be achieved within 24 hours.
- Clean up equipment with mild soap and water.

WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supercedes all other warranties express or implied.